



## Dot 3 Brake Fluid

### Typical Specifications

United Armour Dot 3 Brake Fluid performs a variety of very important functions in the braking systems; it transmits the required power, minimizes corrosion, lubricates, controls proper seal swelling and operates over a wide temperature range.

United Armour Dot 3 Brake Fluid features a minimum boiling point (ERBP) of 450 F, and mixes with all Dot 3 approved brake fluids. This fluid is designed for use in disc, drum and ABS brake systems.

United Armour Dot 3 Brake Fluid meets or exceeds the requirements of the Federal Motor Vehicle Safety Standard (FMVSS) 116 DOT 3, SAE J1703 and ISO 4925.

Applications: FMVSS 116 Dot 3, SAE J1703 and ISO 4925

|  |             |
|--|-------------|
| <b>API Gravity</b>                     | <b>1.05</b> |
| <b>Lbs / Gallon</b>                    | <b>8.70</b> |
| <b>Wet Boiling Point<br/>(ERBP), F</b> | <b>311</b>  |
| <b>Dry Boiling Point<br/>(ERBP), F</b> | <b>446</b>  |
| <b>Viscosity cSt</b>                   |             |
| <b>@ 40 C Max</b>                      | <b>1700</b> |
| <b>@ 100 C Min</b>                     | <b>1.5</b>  |
| <b>PH:</b>                             | <b>9.3</b>  |

\*ERBP = Equilibrium Reflux Boiling Point

The data presented in this specification sheet are believed to be accurate; however, United Armour products shall not be liable for its content and makes no warranty with respect thereto.